


MODEL 108

Insteekdop rond
met schroefdraad



Artikelnummer	A= Buis Uitwendig (mm)	Wanddikte buis (mm)	Doorlopend draadgat	h (mm)	H (mm)	VPE
27000	19	1,0 - 2,0	M 6	5	20	50
27005	20	1,0 - 2,0	M 6	5	20	50
27010	20	1,0 - 2,0	M 8	5	20	50
27015	25	1,0 - 2,0	M 6	5	20	50
27020	25	1,0 - 2,0	M 8	5	20	50
27025	30	1,0 - 2,0	M 8	5	20	50
27030	30	1,0 - 2,0	M 10	5	20	50
27035	32	1,0 - 2,0	M 8	5	20	50
27040	32	1,0 - 2,0	M 10	5	20	50
				5	20	
27045	35	1,0 - 2,0	M 8	5	20	25
27050	35	1,0 - 2,0	M 10	5	20	25
27055	38	1,0 - 2,0	M 8	5	20	25
27060	38	1,0 - 2,0	M 10	5	20	25
27065	38	1,0 - 2,0	M 12	5	20	25
27070	40	1,0 - 2,0	M 8	5	20	25
27075	40	1,0 - 2,0	M 10	5	20	25
27080	40	1,0 - 2,0	M 12	5	20	25
				5	20	
27085	50	1,0 - 2,0	M 8	5	20	10
27090	50	1,0 - 2,0	M 10	5	20	10
27095	50	1,0 - 2,0	M 12	5	20	10
27100	60	1,0 - 2,0	M 8	5	20	10
27105	60	1,0 - 2,0	M 10	5	20	10
27110	60	1,0 - 2,0	M 12	5	20	10

Technische gegevens: Deze insteekdoppen worden vervaardigd uit polyethyleen en zijn standaard zwart.
Deze insteekdoppen zijn voorzien van stalen bus.
Materiaal draadgat: staal verzinkt