


MODEL 87

Inslagdop vierkant
voorzien van metalen insert



Artikelnummer	A= Buitendiameter buis (mm)	Wanddikte buis (mm)	Doorlopend draadbus (mm)	H (mm)	h (mm)	Maximale toelaatbare statistische belasting (kg)	VPE
95600	30 X 30	1,5	M 10	27	6	550	1
95610	30 X 30	1,5	M 12	27	6	550	1
95620	30 X 30	2,0	M 10	27	6	550	1
95630	30 X 30	2,0	M 12	27	6	550	1
95640	40 X 40	1,5	M 10	35	8	600	1
95660	40 X 40	1,5	M 12	35	8	600	1
95670	40 X 40	1,5	M 16	35	8	600	1
95680	40 X 40	1,5	M 20	35	8	600	1
95690	40 X 40	2,0	M 10	35	8	600	1
95700	40 X 40	2,0	M 12	35	8	600	1
95705	40 X 40	2,0	M 14	35	8	600	1
95710	40 X 40	2,0	M 16	35	8	600	1
95715	40 X 40	2,0	M 20	35	8	600	1
95720	40 X 40	3,0	M 12	35	8	600	1
95722	40 X 40	3,0	M 16	35	8	600	1
95725	40 X 40	3,0	M 20	35	8	600	1
95730	50 X 50	1,5	M 12	44	11	1000	1
95740	50 X 50	1,5	M 16	44	11	1000	1
95750	50 X 50	1,5	M 20	44	11	1000	1
95760	50 X 50	2,0	M 12	44	11	1000	1
95770	50 X 50	2,0	M 16	44	11	1000	1
95780	50 X 50	2,0	M 20	44	11	1000	1
95790	50 X 50	2,5	M 12	44	11	1000	1
95800	50 X 50	2,5	M 16	44	11	1000	1
95810	50 X 50	2,5	M 20	44	11	1000	1
95820	50 X 50	3,0	M 12	44	11	1000	1
95830	50 X 50	3,0	M 16	44	11	1000	1
95840	50 X 50	3,0	M 20	44	11	1000	1
95850	60 X 60	2,0	M 16	45	10	1000	1
95860	60 X 60	2,0	M 20	45	10	1000	1
95870	60 X 60	4,0	M 16	45	10	1000	1
95880	60 X 60	4,0	M 20	45	10	1000	1

Technische gegevens: Deze inslagdoppen worden vervaardigd uit polyamide en zijn standaard zwart.
Materiaal doorlopend draad: messing vernikkeld.