


MODEL 9

Insteekdop rond



Artikelnummer	A = buis uitwendig (mm)	Wanddikte buis (mm)	H (mm)	h (mm)	VPE
84021	12	0,8 - 2,0	10,0	4	100
84000	16	0,8 - 2,0	12,4	5,0	100
84034	18	0,8 - 2,0	11,5	5	100
84001	19	0,8 - 2,0	12,4	5	100
84028	20	0,8 - 2,0	11,5	5	100
84024	22	0,8 - 2,0	11,5	5	100
84004	25,4	1,0 - 3,0	12,4	5	100
84006	28	1,0 - 3,0	12,4	5	100
84008	30	1,0 - 3,0	12,4	5	100
84009	32	1,0 - 3,0	12,4	5	100
84027	34	1,0 - 3,0	12,4	5	100
84036	38	1,0 - 3,0	12,4	5	100
84012	38	2,0 - 4,0	14,5	5	100
84031	40	1,0 - 3,0	12,4	5	100
84013	42	1,0 - 3,0	11,5	5	100
84020	42	3,0 - 5,0	11,5	5	100
84032	45	1,0 - 3,0	11,5	5	100
84022	48,3	1,5 - 2,5	17,5	5,5	100
84025	48	2,9 - 4,0	11,5	5	100
84014	50	1,0 - 3,0	14,5	5	100
84016	60	1,0 - 3,0	14,5	5	50
84017	60	3,5 - 5,0	20,1	6	50
84023	70	2,0 - 4,5	21,0	5,3	50
84018	76	2,0 - 4,0	22,0	6	50
84055	80	1,5 - 3,0	17,5	6,5	50
84035	88,9	1,8 - 4,0	21,0	6	50
84060	100	2,0 - 4,5	28,0	6	50
84061	120	2,0 - 4,0	28,0	6	50

Technische gegevens: Deze insteekdoppen worden vervaardigd uit LD polyethyleen en zijn standaard zwart. Ze zijn voorzien van horizontale lamellen rondom voor optimale grip in de buis.